

03/29/01

1002 U.S. PRO

**UTILITY
PATENT APPLICATION
TRANSMITTAL**

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No.

103286-00101

First Inventor or Application Identifier

Wade C. BARNETT

Title

SALT SHOOTER

1002 U.S. PRO

09/819812

03/29/01

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents

ADDRESS TO:

Commissioner for Patents
Box Patent Application
Washington, DC 20231

1. ☒ Fee Transmittal Form (e.g. PTO/SB/17)
(Submit an original and a duplicate for fee processing)
2. ☒ Specification Total Sheets **9**
3. ☒ Drawing(s) (35 U.S.C. 113) Total Sheets **2**
4. ☒ Oath or Declaration Total Pages **2**
 - a. ☒ Newly executed (original or copy)
 - b. ☐ Copy from a prior application (37 C.F.R. §1.63(d))
(for continuation / divisional w/ box 16 completed)
 - i. ☐ **DELETION OF INVENTOR(S)**
Signed statement attached deleting inventor(s) named in
the prior application, see 37 C.F.R. §1.63(d)(2) and
1.33(b).
5. ☐ CD-ROM or CD-R in duplicate, large table or Computer
Program (Appendix)
6. ☐ Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)
 - a. ☐ Computer Readable Form (CRF)
 - b. Specification or Sequence Listing on:
 - i. ☐ CD-ROM or CD-R (2 copies); or
 - ii. ☐ Paper
 - c. ☐ Statements verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

7. ☐ Assignment Papers (cover sheet & document(s))
8. ☐ Application Data Sheet. See 37 CFR 1.76
9. ☐ 37 C.F.R. §3.73(b) Statement ☐ Power of Attorney
(when there is an assignee)
10. ☐ English Translation Document (if applicable)
11. ☒ Information Disclosure
Statement (IDS)/PTO-1449 ☒ Copies of IDS
Citations
12. ☐ Preliminary Amendment
13. ☒ White Advance Serial No. Postcard
14. ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)
15. ☐ Applicant claims small entity status.
See 37 CFR 1.27
16. ☐ Other:

16. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application no.:
Prior application information: Examiner: Group Art Unit:

For CONTINUATION OR DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is
considered a part of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon
when a portion has been inadvertently omitted from the submitted application parts.

17. Amend the specification by inserting before the first line the sentence:

☐ This application is a ☐ Continuation ☐ Division ☐ Continuation-in-part (CIP)
of application Serial No. Filed on

☐ This application claims priority of provisional application Serial No. Filed

18. CORRESPONDENCE ADDRESS

BLANK ROME COMISKY & MCCAULEY LLP
THE FARRAGUT BUILDING
SUITE 1000
900 17TH STREET, NW
WASHINGTON, DC 20006
TEL (202) 530-7400
FAX (202) 463-6915

Name: Charles R. Wolfe, Jr.

Registration No.: 28,680

Signature:

Date: March 29, 2001

FEE TRANSMITTAL for FY 2001

Patent fees are subject to annual revision.

TOTAL AMOUNT OF PAYMENT (\$) 355.00**Complete if Known**

Application Number	New Application
Filing Date	March 29, 2001
First Named Inventor	Wade C. BARNETT
Examiner Name	
Group Art Unit	
Attorney Docket No.	103286-00101

METHOD OF PAYMENT

1. ☒ The Commissioner is hereby authorized to charge indicated fees and credit any overpayments to:
 Deposit Account No. **23-2185**
 BLANK ROME COMISKY & MCCAULEY LLP
- ☒ Charge Any Additional Fee Required Under 37 CFR 1.16 and 1.17
- ☒ Applicant claims small entity status. See 37 CFR 1.27

2. **Payment Enclosed:** ☒ Check ☐ Other
☐ Money Order ☐ Credit Card

FEE CALCULATION**1. Basic Filing Fee**

Large Entity		Small Entity		Fee Description	Fee Paid
Fee Code	Fee (\$)	Fee Code	Fee (\$)		
101	710	201	355	Utility filing fee	355
106	320	206	160	Design Filing Fee	
107	490	207	245	Plant filing fee	
108	710	208	355	Reissue filing fee	
114	150	214	75	Provisional filing fee	
SUBTOTAL (1) (\$)					355

2. EXTRA CLAIM FEES

	Extra claims	Fees From Below	Fee Paid
Total Claims	10	-20** = 2 x 9 =	0
Independent Claims	1	-3** = 0 x 40 =	0
Multiple Dependent			n/a

Large Entity		Small Entity		Fee Description	Fee Paid
Fee Code	Fee (\$)	Fee Code	Fee (\$)		
103	18	203	9	Claims in excess of 20	
102	80	202	40	Independent claims in excess of 3	
107	270	204	135	Multiple dependent claim, if not paid	
109	80	209	40	**Reissue independent claims over original patent	
110	18	210	9	**Reissue claims in excess of 20 and over original patent	
SUBTOTAL (2) (\$)					0

**or number previously paid, if greater; For Reissues, see above

FEE CALCULATION (continued)**3. Additional Fees**


Large Entity		Small Entity		Fee Description	Fee Paid
Fee Code	Fee (\$)	Fee Code	Fee (\$)		
105	130	205	65	Surcharge - late filing fee or oath	
127	50	227	25	Surcharge - late provisional filing fee or cover sheet	
139	130	139	130	Non-English specification	
147	2,520	147	2,520	For filing a request for <i>ex parte</i> reexamination	
112	920*	112	920*	Requesting publication of SIR prior to Examiner action	
113	1,840*	113	1,840*	Requesting publication of SIR after Examiner action	
115	110	215	55	Extension of reply within first month	
116	390	216	195	Extension for reply within second month	
117	890	217	445	Extension for reply within third month	
118	1,390	218	695	Extension for reply within fourth month	
128	1,990	228	945	Extension for reply within fifth month	
119	310	219	155	Notice of Appeal	
120	310	220	155	Filing a brief in support of an appeal	
121	270	221	135	Request for oral hearing	
138	1,510	138	1,510	Petition to institute a public use proceeding	
140	110	240	55	Petition to revive - unavoidable	
141	1,240	242	620	Petition to revive - unintentional	
142	1,240	242	620	Utility issue fee (or reissue)	
143	440	243	220	Design issue fee	
144	600	244	300	Plant issue fee	
122	130	122	130	Petitions to the Commissioner	
123	50	123	50	Processing fee under 37 CFR 1.17(q)	
126	180	126	180	Submission of Information Disclosure Stmt	
581	40	581	40	Recording each patent assignment per property (times number of properties)	
146	710	246	355	Filing a submission after final rejection (37 CFR § 1.129(a))	
149	710	249	355	For each additional invention to be examined (37 CFR § 1.129(b))	
179	710	279	355	Request for Continued Examination (RCE)	
169	900	169	900	Request for expedited examination of a design application	

Other fee (specify)

*Reduced by Basic Filing Fee Paid

SUBTOTAL (3) (\$) 0

BLANK ROME COMISKY & MCCAULEY LLP
 THE FARRAGUT BUILDING
 SUITE 1000
 900 17TH STREET, NW
 WASHINGTON, DC 20006
 TEL (202) 530-7400 FAX (202) 463-6915

Name:	Charles R. Wolfe, Jr.	Registration No.:	28,680
Signature:		Date:	March 29, 2001

SALT SHOOTER

Background of the Invention

Field of the Invention

The present invention relates to devices for spreading salt, sand, and other particles over a surface such as a street or sidewalk to melt ice and snow and for use as a friction (anti-slip) agent.

Description of the Prior Art

When snow and ice are problems on streets and highways, trucks spread sand and salt. The trucks usually use a rotating spreader which flings off particles of sand or salt with centrifugal force. Such centrifugal spreaders have a limited range, and are not suitable to be adapted for hand-held use because the rotating member would hit the user's legs and would need to be held away from the body in an awkward and tiring position.

US Patent 5,542,719 to Nordin discloses a stationary sand spreading device which uses pressurized air to drive sand out of a directed nozzle at the bottom of a cylindrical hopper. The air is fed to the tank from a pressure tank at up to 200 psi. Despite the dangerously high pressure, the sand is likely to jam in the nozzle throat because of the walls of the hopper converge toward the nozzle. The Nordin device is not portable, and could not be made so because of the large air tank required, which must be thick and strong-walled to withstand the high pressure.

In order for a spreader to be portable, it must be light; and to be light, it must be supplied with energy from an outside source (for example, through an extension cord) or must carry energy in a form which is light in weight (such as gasoline). However, this is not disclosed in the prior art.

The prior art does not disclose a hand-held or portable sand or salt spreader, nor does it disclose any blower which is adapted to spread salt, absorbent particles, friction agents, or the like.

Summary of the Invention

The present invention has an object of providing a portable or hand-held device which is capable of broadcasting salt, sand, and other friction-increasing particles over a surface such as a street or sidewalk to prevent slips, falls, or vehicle skids. The spreader of the invention is intended to be, preferably, light enough in weight so that it may be operated while hand-held.

Another object is a portable spreader which can broadcast particles in a wide "shotgun" pattern and includes a base, so that it can sit in stable attitude on a surface and operate without attention to cover a broad area with friction particles.

A further object is a spreader that uses high-speed air to pick up and throw particles of salt, sand, absorbent clay particles such as KITTY LITTER, gravel, or any other type of friction-enhancing particulate, powder or granule, enabling the user to evenly cover a surface with the particles.

The present invention relies on the characteristic of wind to pick and carry particles. A motor and blower are used to generate an air stream that picks up and carries friction particles, which are then blown through a nozzle and spewed out to scatter over the surface to be friction-treated. In a preferred embodiment, the air stream flows at least partially through the particles resting in a storage chamber.

With these and other objects, advantages and features of the invention that may become hereinafter apparent, the nature of the invention may be more clearly understood by reference to the following detailed description of the invention, the appended claims and to the several drawings attached herein.

Brief Description of the Drawings

FIG. 1 is an exploded perspective view.

FIG. 2 is a partial cross-sectional view on lines II-II of Fig. 1.

FIG. 3 is a perspective view.

FIG. 4 is a perspective view.

Detailed Description of the Invention

Fig. 1 shows a preferred embodiment of the present invention, a hand-held or portable spreader 10 that blows particles over a surface (not shown). The spreader 10 is shown separated into a lower part including a conduit 200 and a storage chamber 100, which holds the particles (seen in Fig. 2). The bottom of the storage chamber 190 serves as a stable base, and optionally includes stabilizing feet 192.

Above the storage chamber 100 is an air blower structure 300 including a lid 310, an impeller housing 320 containing an air impeller 325 (seen in Fig. 2), and a second nozzle conduit 330 merging into a nozzle 340. Above the housing 320 is a motor 400 which drives the air impeller 325, preferably by direct drive; a gasoline engine (not shown) is an alternative. A grip 500 is provided, which may include a power connector 540 adapted to mate with an extension cord C.

An on/off switch 550 is preferably mounted on the grip 500. The switch 550 preferably includes a lock or is of childproof design.

A catch 112, on the upper rim of the storage chamber 100, cooperates with a mating catch member on the rim flange of the lid 310 (not visible) to hold the spreader 10 together in the assembled position (seen in Fig. 2).

The lid 310 includes a plurality of holes 312 which admit air to the storage chamber 100 when the lid 310 is secured onto the storage chamber 100.

A flat disk 700, shown in Fig. 3, may be loosely mounted above lid 310 for rotation along the outer walls of conduit 200 to control the intake airflow through lid 310. The disk 700 preferably is equal in size, construction, and dimension to the horizontal portion of lid 310, and perforated with holes 712, identically to the plurality of the holes 312 in lid 310. To vary the airflow, the disk has a small handle 730 in a convenient location along the periphery for the purpose of rotating the disk, and thereby aligning or mis-aligning the holes 712 and 312. This disk will preferably not have any vertical sides as does lid 310.

Fig. 2 shows the path of the air admitted through the holes 312. (Disk 700 is not shown in Fig. 2.) The air passes downward through a mass of particles P loaded into the storage

chamber 100, which is seen to be generally shaped as an annulus of a cylinder. Located preferably at the bottom of the storage chamber is an annular gap which serves as an orifice 120.

Preferably, the orifice is generally annular and extends at least partially around the conduit; that is, the orifice may comprise a series of holes or openings disposed along a circumference or portions of a circumference, or, it may comprise an opening in the form of a band or annulus, bordered by two continuous rims passing all the way around or part of the way around the conduit.

The cross sectional area of the orifice is preferably smaller than the cross sectional area of the annular storage chamber 100, so that as air approaches the orifice 120 it speeds up and is able to lift particles P. The central conduit 200 has an internal diameter such that the air stream carries the particles P upward to the air blower, which preferably comprises the vane impeller 325 and impeller housing 320. The vane impeller 325 is preferably of the centrifugal type, and the housing 320 is preferably somewhat spiral in shape. The spiral shape merges internally into a second nozzle conduit 330. The air blower maintains an air stream velocity sufficient to carry the particles P through both conduits 200, 330 and spew them forth.

The vanes of the impeller 325 are preferably curved, so that when the air stream impinges on the vanes of the impeller 325 from an axial direction as illustrated, the particles will ricochet outward and acquire an additional velocity parallel to the air flow.

At the bottom of the conduit 200, a swirling cloud of particles may form. Lighter particles will be selectively drawn upward toward the impeller vanes, leaving larger particles in the bottom of the conduit. These lighter particles have less momentum and will slow down faster in still air than larger particles would, but, they are carried along with the air stream; at first a larger proportion of smaller particles will be shot from the nozzle. As the storage chamber empties, the air stream velocity will increase, due to a shorter air flow path through the particles in the storage chamber and consequent decreased air resistance, and the larger particles will be picked up and shot out. These larger particles will shoot farther due to their higher speed and greater momentum.

An alternative embodiment, which is not presently preferred and is not illustrated, provides a draft gate at the bottom of the conduit 200; if included in the present invention, the

any draft gate should be adapted to close. As experimented with, the draft gate caused clumping with rock salt.

It is noted that clumps of rock salt, if drawn from the storage chamber 100 through the conduit 200 by a high velocity air flow, should shatter upon impact with the vanes of the impeller 325. Those clumps would then be sufficiently reduced in size to permit expulsion of residual pieces through nozzles 330 and 340. Impeller 325 is preferably constructed of a material resistant to the corrosive properties of rock salt, and of sufficient strength to reduce larger particles P to a size consistent with efficient distribution through the channels of the present Shooter.

The invention also contemplates an adjustable choke-like device on the end of nozzle 340, or a permanent choke (a nozzle with choke is shown in Fig. 4). If the convergence of a choke is too steep, the clogging behind such a choke-like device is to be anticipated. However, a cone-shaped attachment, slightly reducing the diameter of nozzle 340 and causing accelerated airflow and increased propulsion distance, may be advantageous and is within the scope of the invention.

The vibrations from the impeller and motor help to break up any particle jams at the orifice, thus keeping up a steady particle delivery rate. The present invention may also include mechanisms similar to that of a coal grate, or means for providing additional vibration, to avoid jamming at the orifice.

All parts of the invention that come into contact with the particles P are preferably constructed of corrosion- and abrasion-resistant materials able to resist rock salt, calcium chloride, and similar substances.

Fig. 4 shows an embodiment of the spreader 10' with an alternatively-shaped storage chamber 100' with a slightly choked nozzle 340'. The generally kidney-shaped storage chamber 100' may optionally be made of flaccid material such as fabric, and/or may include air holes 110' analogous to the holes 310 of Figs. 1-2. Alternatively, the fabric may be porous to the extent that distinct air holes are not needed.

The embodiment of Fig. 3 is preferably lighter than the embodiment of Figs. 1-3, but is similar in function and general construction.

A removable nylon cloth shoulder strap 600, preferably constructed of 2" wide ballistic nylon, may be affixed to the top of the spreader 10' for use in supporting the combined weight of the invention and loaded particles P. This strap 600 preferably has a 3" wide x 8" long shoulder pad 690 through which the strap 600 runs, and which is adjustable along the length of the strap for proper positioning. The overall length of the strap should be adjustable from 48" to 72" in order to accommodate various users of various heights, and to afford the user a wide array of comfort settings.

Preferably, the strap is attached at a point generally above the center of gravity of the spreader 10', for ease of directing the nozzle 340'. Also, the kidney-shaped chamber 100' can be shaped so that remaining particles P will collect in such a manner that the balance of the spreader is maintained.

The strap 600 is preferably affixed to through the use of a brass or nylon spring-loaded catch 610, clipping to a D-ring permanently attached to the spreader 10'. The spring-loaded catch will preferably be similar to those used on soft-sided luggage shoulder straps.

Alternatively, the forward end of the strap may be attached to the nozzle 340' by wrapping it once around the shaft of nozzle 340' (not shown), and affixing it to itself through the use of a spring loaded catch, identical to the previously-described end attachment. This forward anchor point can be slid freely along the length of nozzle 340' to the user's comfort.

The strap 600 can also be used with the embodiment of Figs. 1-3.

Although certain presently preferred embodiments of the present invention have been specifically described herein, it will be apparent to those skilled in the art to which the invention pertains that variations and modifications of the various embodiments shown and described herein may be made without departing from the spirit and scope of the invention. Accordingly, it is intended that the invention be limited only to the extent required by the appended claims and the applicable rules of law.